

Earth-Rite TELLUS

Technical Specification (FM/FMc)



- Bright flashing green LED indicates positive grounding to operators and production managers.
- Volt free relay contact to interlock process machinery or alarms if positive ground connection is lost.
- Approved for installation in the majority of hazardous locations (FM & FMc).
- Cost effective flexible and simple installation close to the process.
- Interfaces with full range of Cen-Stat clamps, connectors and cables to suit a variety of grounding situations.

Ordering Information

Part No.	Ordering Description
TEL2A2B	Earth-Rite TELLUS 230Vac; GAT-IP Clamp; 5m Blue Spiral Cable
TEL2B2B	Earth-Rite TELLUS 110Vac; GAT-IP Clamp; 5m Blue Spiral Cable



Technical Specification for FM & FMc Version

TELLUS Monitoring Unit

Power Supply and Power Rating	110V - 230V \pm 10% 50/60 Hz; 9 Watts
Operational Ambient Temperature Range	-20°C to +40°C
Weight	3kgs
Enclosure Construction	Thermo-Plastic
Operational Earth Resistance	<100 Ohm, switchable <10 Ohm
Ingress Protection	IP65
Control Contact Rating	1 voltage free switch contact 240Vac / 2A / $\cos\phi > 0.7$ 120Vac / 4A / $\cos\phi > 0.7$ 40Vdc / 2A resistive load
Connection Status Indicator LEDs	Flashing Green LED indicates positive static connection <10 Ohm
Cable Entries	3 x 20mm diameter holes in bottom of control unit
Certification	FM 3032464: Class I, II & III, Division 1, Groups A, B, C, D, E, F & G FMC 3032464C: Class I, II & III, Division 1, Groups A, B, C, D, E, F & G

TELLUS Indicator

Enclosure	GRP with carbon loading
Terminals	6 x 4mm sq. conductor capacity
Stowage Device	Insulated 20mm diameter pin
Cable Entries	4 x 20mm Nylon compression gland for spiral cable
Certification	FM 3032464: Class I, II & III, Division 1, Groups A, B, C, D, E, F & G FMC 3032464C: Class I, II & III, Division 1, Groups A, B, C, D, E, F & G
Operational Ambient Temperature Range	-40°C to +60°C
Earthing Clamp	
Clamp Design	2 pole with stainless steel tips
Body	Cast Alloy
Cen-Stat Retractable Cable	
Cover	Blue Hytel sheath (static dissipative, chemical & abrasion resistant)
Conductors	2 x 1.00mm ² copper

The Earth-Rite TELLUS forms part of the Earth-Rite range of Static Grounding and Bonding Equipment available from Newson Gale



Leading the way in hazardous area static control

www.newson-gale.com

Newson Gale Inc
460 Faraday Avenue
Unit B, Suite 1
Jackson, NJ 08527
USA

Tel: +1 732 987 7715
Fax: +1 732 791 2182

Email: groundit@newson-gale.com

Newson Gale Ltd
Omega House
Private Road 8
Colwick, Nottingham
NG4 2JX, UK

Tel: +44 (0)115 940 7500
Fax: +44 (0)115 940 7501

Email: groundit@newson-gale.co.uk